

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application. Claims 1, 8, 9, 13, 20, 21, 25, 32, and 33 have been amended, and claims 7, 19, and 31 have been canceled herein.

**Listing of Claims:**

1. (currently amended) A system for monitoring a networked computer service for fault recovery, the networked computer service comprising a set of features, the system comprising:

an input interface to receive network status data from a network monitor monitoring a computer services network;

a control engine, the control engine communicating with the input interface to receive the network status data and automatically generate control commands to dynamically adjust the set of features based on a fault condition detected in the network status data for one or more features within the set of features; and

an output interface, communicating with the control engine and the computer services network, the output interface communicating the control commands to the computer services network to dynamically adjust the set of features by deactivating the one or more features having a fault condition while maintaining active features in the set of features to continue to provide the networked computer serviceto respond to the fault condition.

2. (original) A system according to claim 1, wherein the computer services network comprises an Internet service.

3. (original) A system according to claim 2, wherein the Internet service comprises a search service.

4. (original) A system according to claim 1, wherein the network status data comprises at least one of page latency data, processor utilization data, connection data and storage data.

5. (original) A system according to claim 1, wherein the fault condition comprises a failure of the network status data to meet a performance threshold.

6. (original) A system according to claim 5, wherein the performance threshold comprises a minimum response time for a user of the networked computer services.

7. (canceled)

8. (currently amended) A system according to claim 1[[7]], wherein the control engine reactivates at least a portion of the one or more features or restores the affected servicee upon restoration of predetermined network status data.

9. (currently amended) A system according to claim 1[[7]], wherein the control engine alters the operation of at least one active featureanother service in compensation for deactivating the one or more featuresthe affected service.

10. (original) A system according to claim 1, wherein the control engine comprises a rules-based decisioning engine.

11. (original) A system according to claim 10, wherein the rules-based decisioning engine interfaces to a control database storing at least one of the network status data and a set of service fault rules.

12. (original) A system according to claim 1, further comprising a manual override selector, the manual override selector permitting an operator to override the control commands generated by the control engine.

13. (currently amended) A method for monitoring a networked computer service for fault recovery, the networked computer service comprising a set of features, the method comprising:

receiving network status data from a network monitor monitoring a computer services network;

automatically generating control commands to deactivate one or more features based on a fault condition in the network status data while maintaining active features in the set of features to continue to provide the networked computer service; and

communicating the control commands to the computer services network to respond to the fault condition by deactivating the one or more features while maintaining the active features in the set of features, thereby allowing a user accessing the networked computer service to continue to receive the networked computer service with the one or more features having a fault condition removed.

14. (original) A method according to claim 13, wherein the computer services network comprises an Internet service.

15. (original) A method according to claim 14, wherein the Internet service comprises a search service.

16. (original) A method according to claim 13, wherein the network status data comprises at least one of page latency data, processor utilization data, connection data and storage data.

17. (original) A method according to claim 13, wherein the fault condition comprises a failure of the network status data to meet a performance threshold.

18. (original) A method according to claim 17, wherein the performance threshold comprises a minimum response time for a user of the networked computer services.

19. (canceled)

20. (currently amended) A method according to claim 13[[19]], further comprising a step of reactivating the one or more features ~~or restoring the affected service~~ upon restoration of predetermined network status data.

21. (currently amended) A method according to claim 13[[19]], further comprising a step of altering the operation of at least one active feature~~another service~~ in compensation for deactivating the one or more features~~the affected service~~.

22. (original) A method according to claim 13, wherein the step of automatically generating comprises executing a rules-based decisioning engine.

23. (original) A method according to claim 22, wherein the rules-based decisioning engine interfaces to a control database storing at least one of the network status data and a set of service fault rules.

24. (original) A method according to claim 13, further comprising a step of manually overriding the automatically generated control commands.

25. (currently amended) A networked computer service comprising a set of features, the networked computer service being monitored for fault management according to a method of:

receiving network status data from a network monitor monitoring a computer services network;

automatically generating control commands to deactivate one or more features based on a fault condition in the network status data while maintaining active features in the set of features to continue to provide the networked computer service; and

communicating the control commands to the computer services network to respond to the fault condition by deactivating the one or more features while maintaining the active features in the set of features, thereby allowing a user accessing the networked computer service to continue to receive the networked computer service with the one or more features having a fault condition removed.

26. (original) A networked computer service according to claim 25, wherein the computer services network comprises an Internet service.

27. (original) A networked computer service according to claim 26, wherein the Internet service comprises a search service.

28. (original) A networked computer service according to claim 25, wherein the network status data comprises at least one of page latency data, processor utilization data, connection data and storage data.

29. (original) A networked computer service according to claim 25, wherein the fault condition comprises a failure of the network status data to meet a performance threshold.

30. (original) A networked computer service according to claim 29, wherein the performance threshold comprises a minimum response time for a user of the networked computer services.

31. (canceled)

32. (currently amended) A networked computer service according to claim 25[[31]], wherein the method further comprises a step of reactivating the one or more features or restoring the affected service upon restoration of predetermined network status data.

33. (currently amended) A networked computer service according to claim 25[[32]], wherein the method further comprises a step of altering the operation of at least one active feature ~~another service~~ in compensation for deactivating the one or more features ~~the affected service~~.

34. (original) A networked computer service according to claim 25, wherein the step of automatically generating comprises executing a rules-based decisioning engine.

35. (original) A networked computer service according to claim 34, wherein the rules-based decisioning engine interfaces to a control database storing at least one of the network status data and a set of service fault rules.

36. (original) A networked computer service according to claim 25, wherein the method further comprises a step of manually overriding the automatically generated control commands.